




PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : H04H 1/00		A1	(11) International Publication Number: WO 99/14874 (43) International Publication Date: 25 March 1999 (25.03.99)
(21) International Application Number: PCT/SE98/01624 (22) International Filing Date: 14 September 1998 (14.09.98) (30) Priority Data: 9703331-0 16 September 1997 (16.09.97) SE (71) Applicant (for all designated States except US): TERACOM AB (SE/SE); P.O. Box 17666, S-118 92 Stockholm (SE). (72) Inventors; and (75) Inventors/Applicants (for US only): REBHAN, Richard (SE/SE); Rödabergsgatan 12, S-113 33 Stockholm (SE). KARLSSON, Pierre (SE/SE); Bäckadalsvägen 3, S-147 37 Huddinge (SE). RUOTTINEN, Per [-/SE]; Skeppargatan 83, S-115 30 Stockholm (SE). OSSFELDT, Jan (SE/SE); Diamantgöngen 219, S-135 49 Tyresö (SE). (74) Agents: GRAUDUMS, Valdis et al.; Albihns Patentbyrå Göteborg AB, P.O. Box 142, S-401 22 Göteborg (SE).		(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, GH, GM, HR, HU, ID, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).	
		Published With international search report. Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.	

(54) Title: **METHOD AND DEVICE FOR CHANGE OF RECEPTION FREQUENCY IN A DIGITAL AUDIO BROADCASTING SYSTEM RECEIVER**

(57) Abstract

A method and a device for test receiving alternative frequencies without interrupting the reception of DAB frames from the current reception frequency in a DAB receiver. A DAB frame comprises a null symbol which is used to do a first very coarse synchronisation of the receiver to the transmitted signals. According to the invention, test receptions of alternative frequencies occur during the currently received programme's null symbols. By performing test receptions during the current programme's null symbols the current programme is not interrupted at all during the test receptions. A subsequently determined frequency changeover can thereafter, with a high probability, be performed without any noticeable interruption.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakhstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

WO 99/14874

PCT/SE98/01624

METHOD AND DEVICE FOR CHANGE OF RECEPTION FREQUENCY IN A DIGITAL AUDIO BROADCASTING SYSTEM RECEIVER

FIELD OF THE INVENTION

5 The present invention relates generally to a method and a
device for change of reception frequency in a radio-
frequency receiver, especially mobile radiofrequency
receivers, in the intersection area between radio
broadcasting regions with different broadcasting
10 frequencies, especially in a radiofrequency receiver for a
digital audio broadcasting system (DAB).

BACKGROUND TO THE INVENTION

15 A conventional mobile FM-radio receiver, such as a car
radio, has to change reception frequency when moving from
one broadcasting area/region covered by one transmitter to
another broadcasting area/region covered by another
transmitter. Adjacent FM-radio broadcasting transmitters
cannot transmit with the same radiofrequency, because if
they did, due to the analog modulation of the
20 radiofrequency signals, cross interference between the
adjacent transmitters would arise. Therefore adjacent/
different FM-radiobroadcasting transmitters, independently
if they broadcast different information in the same area or
the same information in adjacent areas, transmit with
25 sufficiently different frequencies to avoid cross
interference.

Frequencies are reused in broadcast areas that are
sufficiently distant from each other so that cross
interference does not occur. The FM-radio broadcasting

WO 99/14874

PCT/SE98/01624

2

system uses a relatively small bandwidth for each channel, this facilitates frequency changeover when a shift from one broadcasting transmitter to another is desired due to, for example, a transfer from one transmitter's broadcasting area to another.

Probably one of the first solutions for relieving, for example, a car driver from the burden of changing reception frequency when traveling from one FM-radiobroadcasting area to another was to, when the field strength of the currently received signal had fallen below a preset value, let the radio receiver scan the frequency area closest to the reception frequency in order to find an alternative reception frequency. An improvement to this is to let the FM-radio receiver measure the field strengths of several alternative reception frequencies and then change over to the one with the highest field-strength. The car driver, in these examples, does not have to fiddle about with the radio receiver but the reception gets interrupted while the receiver scans and possibly measures the alternative frequencies.

Radio data system (RDS) is an enhancement of and implemented into many analog FM-radio broadcasting systems. RDS provides certain improvements to the functioning of frequency changeover. An RDS FM-radio receiver will usually have the capability to store a list, received via RDS, of alternative frequencies for the current programme, for example a regionally or nationally broadcasted programme. When the received audio level is low, an RDS FM-radio will quickly change reception frequency to one of the alternative frequencies to thereby measure the alternative frequency's field strength in a test reception. The listener will usually not notice these short test receptions of alternative frequencies as the system utilizes short silences in speech or music in the current

WO 99/14874

PCT/SE98/01624

3

programme. The audio output is preferably muted during the test receptions as well. The results of the test receptions will usually be the inputs to some sort of decision unit which will decide when and to which
5 alternative frequency a frequency changeover should take place. This will probably, most of the time, be an unnoticeable function for the user, as it should be, letting, for example, a driver devote his full concentration on driving.

10 To avoid some disadvantages that are inherent in an analog FM-radio broadcasting system a new digital radio broadcasting system, digital audio broadcasting (DAB), has emerged. DAB which uses coded orthogonal frequency
15 division multiplexing (COFDM) modulation was primarily intended as a single frequency network (SFN) to thereby broadcast four to twenty different nationally or regionally distributed audio programmes, the number depending on audio quality, i.e. coded audio rate, and the desired protection level. In a single frequency network a DAB-radio receiver
20 does not have to switch reception frequency when travelling between regions covered by different transmitters as they all transmit the same programmes/ information with the same frequency.

25 However, there probably will evolve a demand from local and community broadcasters to use the DAB system to thereby take advantage of the benefits that the DAB system provides over the older analog FM-radio system. These regional, local, and/or community DAB broadcasting regions will require a frequency distribution plan equivalent to that of
30 the FM-broadcasting system. As the DAB system will allow four to twenty different programmes to be broadcast simultaneously and as probaly not all of these are required for local/ community broadcasters then one or more of these can be of a regional or national type. Even though the DAB

WO.99/14874

PCT/SE98/01624

4

5 broadcasting system was not envisaged as anything else than an SFN, there has now, in a DAB system, arisen a need to be able to switch/changeover reception frequency without the involvement of the listener or actually disturbing the listener with an unwarranted silence.

10 As mentioned, the DAB system uses a COFDM modulation technique which provides a robust method of information transfer. But due to, for example, the interleaving and the decoding of the digital data stream, the digital data stream cannot be interrupted for a test reception of an alternative frequency to thereby implement an unnoticeable method of test receiving alternative frequencies equivalent to that of the RDS system mentioned above. DAB is spectrally very robust but temporally somewhat more
15 fragile. DAB can lose some sub carriers, due to, for example, fading, some of the time but the data stream cannot be cut off for a time period necessary for a test reception of alternative frequencies.

20 To somewhat provide a solution to the problem of finding alternative frequencies for a current programme, the DAB system broadcasts alternative frequencies of the current programme so that a list of these can be maintained in the receiver in a manner comparable to that of the RDS system. The DAB receiver will, in accordance to the methods used
25 previously in other systems, when the field strength of the received programme falls below a preset threshold or according to a tendency of the field strength, interrupt the reception of the programme and perform test receptions of the alternative frequencies in the list. The reception
30 of the current programme is unfortunately interrupted for a time interval, which can be considered annoying. As an alternative, a DAB receiver can arbitrarily choose one of the alternative frequencies on the list and perform a frequency change inbetween two information frames. If such

WO 99/14874

PCT/SE98/01624

5

5 a method is used then there exists a certain probability that the correct frequency is selected and that therefore no interruption will occur. On the other hand there is also a high probability that the frequency is incorrect and that several frequency changes has to be performed with a considerable interruption of the programme as a result of this.

SUMMARY OF THE INVENTION

10 An object of the invention is to define a method and a device for providing an automatic change of reception frequency in a DAB receiver, especially a mobile DAB receiver, without any interruption or only a practically unnoticeable interruption of the current programme.

15 Another object of the invention is to define a method and a device which are able to deliver a preferable alternative frequency in a DAB receiver for a current programme without interrupting the current programme.

20 A further object of the invention is to define a method and a device which are able to test receive an alternative reception frequency for evaluation purposes in a DAB receiver without interrupting the currently received programme/ information.

25 A still further object of the invention is to define a method and a device which are able perform an automatic change of reception frequency to one alternative frequency which is preferable over the current frequency, when a DAB receiver is in the intersection between two or more broadcasting areas with different transmitter frequencies which transmit at least one common programme or programme

WO 99/14874

PCT/SE98/01624

6

type, without interrupting the received programme for test receptions of the alternative frequencies.

The above-mentioned objects are achieved in accordance with the invention by a method of test receiving alternative frequencies without interrupting the reception of the information carrying part of DAB frames from the current reception frequency in a DAB receiver. A receiver for carrying out the method according to the invention is also provided. A DAB frame comprises a null symbol which is used to do a first very coarse synchronisation of the receiver to the transmitted signals. After the initial synchronisation, the phase reference symbols, which are the subsequent symbols, synchronises the receiver with the transmitter. Initially the null symbol was intended to be completely empty, but in later revisions of the DAB standard, the null symbol comprises a specially coded transmitter identification information (TII). The TII is transmitted with a lower average power value during the symbol time to thereby still allow the null symbol to correctly function as a null symbol. According to the invention, test receptions of alternative frequencies are performed during the currently received programme's null symbols. A test reception performs a switch of the reception frequency from the currently received frequency to a frequency which is to be tested, and at the end of the test reception the reception frequency is switched back to the originally received frequency, i.e. the currently received frequency, unless a permanent switch of frequency is determined. A switch of reception frequency has to be performed during test receptions because according to the invention only one reception chain is used. According to the invention a test reception is only performed as not to interfere with the reception of the currently received programme, i.e. the information carrying parts of the DAB frame. If the null symbols of the alternative frequencies

WO 99/14874

PCT/SE98/01624

7

occur at the same time as the current programme's null symbols the received TII of the alternative frequencies are used for evaluation purposes. By performing test receptions during the current programme's null symbols the
 5 current programme is not interrupted at all during the test receptions. A subsequently determined frequency changeover can thereafter, with a high probability, be performed without any noticeable interruption.

The aforementioned objects are also achieved according to
 10 the invention by a method for providing an automatic change of reception frequency in a digital audio broadcasting (DAB) system receiver between a currently received frequency and a, from a field strength point of view, preferable alternative reception frequency. The receiver
 15 only having one reception chain for DAB. The preferable alternative reception frequency might well be the currently received frequency. The currently received frequency is in a digital audio broadcasting system format comprising transmission frames where each transmission frame comprises
 20 multicarrier symbols and a coarse synchronisation symbol in the form of a null symbol. The currently received frequency is meant to denote the frequency that is received when the procedure of the method according to the invention commences. The method comprises a number of steps in a
 25 digital audio broadcasting receiver. First of all, a list of alternative frequencies is determined. The list might consist of only one alternative frequency or a plurality. The currently received frequency can preferably be included in the list. The list might be assembled from all or
 30 selected frequencies from those included in the information received by the currently received DAB transmission, preprogrammed frequencies, one or more random frequencies generated, for example, from a random generator, all or
 35 selected frequencies in the neighbourhood of the currently received frequency, or all or selected frequencies in the

WO 99/14874

PCT/SE98/01624

8

frequency range of the digital audio broadcasting receiver or a combination of any of these possibilities. When it has been determined what frequencies should be test received then test receptions of the alternative frequencies on the determined list are systematically performed. The test receptions are mainly performed during the null symbols of the digital audio broadcasting frames of the currently received frequency. Preferably the test receptions are only performed during the null symbols of the currently received frequency or alternatively the test receptions are performed during the null symbols and at least during part of at least one phase reference symbol of the currently received frequency. After or interleaved with the test receptions of the alternative frequencies the test receptions of the alternative frequencies on the determined list are evaluated. In one preferred method the alternative frequencies on the determined list are systematically test received at least once each before the evaluation of the test receptions. In another preferred method the alternative frequencies on the determined list are systematically test received only once each before the evaluation of the test receptions. In yet another preferred embodiment the alternative frequencies on the determined list are systematically test received at least twice each before the evaluation of the test receptions and the evaluation of the test receptions is based on calculated tendency of the field strength of each alternative frequency on the determined list. Based on the evaluation of the test receptions of the alternative frequencies on the determined list, which one of the alternative frequencies or the currently received frequency is preferable from a field strength point of view is determined. The currently received frequency might, as was mentioned previously, be included in the list of determined alternative frequencies, but it is important not to forget it as it might be the best one for the time being. When it

WO.99/14874

PCT/SE98/01624

9

has been determined which frequency is preferable the reception frequency is changed to the determined preferable reception frequency. Preferably the changing of reception frequency to the determined preferable reception frequency is performed/ executed inbetween two digital audio broadcasting frames of the currently received frequency. The determined preferable reception frequency might be the currently received frequency and in such a case the change of frequency is not to another frequency. The method according to the invention thereby enables an automatic change of reception frequency in a digital audio broadcasting receiver without any interruption or only a practically unnoticeable interruption of the current programme. At least one alternative frequency on the determined list can advantageously be a digital audio broadcasting system transmission. The transmission frames of the different digital audio broadcasting systems preferably comprise transmitter identification information during the null symbols and which frames are preferably in principle synchronised. At least one of the alternative frequencies on the determined list can advantageously be of the FM or AM radio broadcasting type and in a preferred embodiment the evaluation of the test receptions further comprises the step of determining what type of broadcasting system each alternative frequency broadcasts.

The aforementioned objects are also achieved by a method for test receiving alternative reception frequencies in a digital audio broadcasting (DAB) system receiver for the purpose of being able to determine a, from a field strength point of view, preferable alternative reception frequency. The receiver tuned to a currently received frequency in a digital audio broadcasting system format receives a current programme/ information. The DAB format of the currently received frequency comprises transmission frames. Each transmission frame comprises multicarrier symbols and a

WO 99/14874

PCT/SE98/01624

10

coarse synchronisation symbol in the form of a null symbol.
The currently received frequency is meant to denote the frequency that is received when the procedure of the method according to the invention commences. The method comprises
5 a number of steps in a digital audio broadcasting receiver. First of all, a list of alternative frequencies is determined. The list might consist of only one alternative frequency or a plurality. The currently received frequency can preferably be included in the list. The list might be
10 assembled from all or selected frequencies from those included in the information received by the currently received DAB transmission, preprogrammed frequencies, one or more random frequencies generated, for example, from a random generator, all or selected frequencies in the
15 neighbourhood of the currently received frequency, or all or selected frequencies in the frequency range of the digital audio broadcasting receiver or a combination of any of these possibilities. When it has been determined what frequencies should be test received then test receptions of
20 the alternative frequencies on the determined list are systematically performed. The test receptions are mainly performed during the null symbols of the digital audio broadcasting frames of the currently received frequency. Preferably the test receptions are only performed during
25 the null symbols of the currently received frequency or alternatively the test receptions are performed during the null symbols and at least during part of at least one phase reference symbol of the currently received frequency. After or interleaved with the test receptions of the
30 alternative frequencies the test receptions of the alternative frequencies on the determined list are evaluated. In one preferred method the alternative frequencies on the determined list are systematically test received at least once each before the evaluation of the test receptions. In
35 another preferred method the alternative frequencies on the determined list are systematically test received only once

WO 99/14874

PCT/SE98/01624

11

each before the evaluation of the test receptions. In yet another preferred embodiment the alternative frequencies on the determined list are systematically test received at least twice each before the evaluation of the test

5 receptions and the evaluation of the test receptions is based on calculated tendency of the field strength of each alternative frequency on the determined list. Based on the evaluation of the test receptions of the alternative frequencies on the determined list, which one of the

10 alternative frequencies or the currently received frequency is preferable from a field strength point of view is determined. The currently received frequency might, as was mentioned previously, be included in the list of determined alternative frequencies, but it is important not to forget

15 it as it might be the best one for the time being. The method according to the invention thereby enables the delivery of a preferable alternative frequency in a digital audio broadcasting receiver for a current programme/ information without interrupting the current programme/ information.

20 At least one alternative frequency on the determined list can advantageously be a digital audio broadcasting system transmission. The transmission frames of the different digital audio broadcasting systems preferably comprise transmitter identification information during the null symbols and which frames are preferably in principle

25 synchronised. At least one of the alternative frequencies on the determined list can advantageously be of the FM or AM radio broadcasting type and in a preferred embodiment the evaluation of the test receptions further comprises the

30 step of determining what type of broadcasting system each alternative frequency broadcasts.

The aforementioned objects are also achieved by a method for test receiving alternative reception frequencies in a digital audio broadcasting system receiver for the purpose

35 of being able to evaluate alternative reception

WO 99/14874

PCT/SE98/01624

12

frequencies. The receiver tuned to a currently received frequency in a digital audio broadcasting system format receives a current programme/ information. The DAB format of the currently received frequency comprises transmission frames. Each transmission frame comprises multicarrier symbols and a coarse synchronisation symbol in the form of a null symbol. The currently received frequency is meant to denote the frequency that is received when the procedure of the method according to the invention commences. The method comprises a number of steps in a digital audio broadcasting receiver. First of all, a list of alternative frequencies is determined. The list might consist of only one alternative frequency or a plurality. The currently received frequency can preferably be included in the list. The list might be assembled from all or selected frequencies from those included in the information received by the currently received DAB transmission, preprogrammed frequencies, one or more random frequencies generated, for example, from a random generator, all or selected frequencies in the neighbourhood of the currently received frequency, or all or selected frequencies in the frequency range of the digital audio broadcasting receiver or a combination of any of these possibilities. The selection can, for example, be based on the geographical location of the corresponding receiver. When it has been determined what frequencies should be test received then test receptions of the alternative frequencies on the determined list are systematically performed. The test receptions are mainly performed during the null symbols of the digital audio broadcasting frames of the currently received frequency. Preferably the test receptions are only performed during the null symbols of the currently received frequency or alternatively the test receptions are performed during the null symbols and at least during part of at least one phase reference symbol of the currently received frequency. After or interleaved with the test

WO 99/14874

PCT/SE98/01624

13

receptions of the alternative frequencies the test
receptions of the alternative frequencies on the determined
list are evaluated. In one preferred method the
alternative frequencies on the determined list are
5 systematically test received at least once each before the
evaluation of the test receptions. In another preferred
method the alternative frequencies on the determined list
are systematically test received only once each before the
evaluation of the test receptions. In yet another
10 preferred embodiment the alternative frequencies on the
determined list are systematically test received at least
twice each before the evaluation of the test receptions and
the evaluation of the test receptions is based on
calculated tendency of the field strength of each
15 alternative frequency on the determined list. The method
according to the invention thereby enables an evaluation of
alternative frequencies on a determined list without
interrupting the currently received programme/information.
At least one alternative frequency on the determined list
20 can advantageously be a digital audio broadcasting system
transmission. The transmission frames of the different
digital audio broadcasting systems preferably comprise
transmitter identification information during the null
symbols and which frames are preferably in principle
25 synchronised. At least one of the alternative frequencies
on the determined list can advantageously be of the FM or
AM radio broadcasting type and in a preferred embodiment
the evaluation of the test receptions further comprises the
step of determining what type of broadcasting system each
30 alternative frequency broadcasts.

The aforementioned objects are also achieved by a method
for test receiving an alternative reception frequency in a
digital audio broadcasting system receiver for the purpose
of being able to evaluate an alternative reception
35 frequency. The receiver tuned to a currently received

WO 99/14874

PCT/SE98/01624

14

frequency in a digital audio broadcasting system format receives a current programme/ information. The DAB format of the currently received frequency comprises transmission frames. Each transmission frame comprises multicarrier symbols and a coarse synchronisation symbol in the form of a null symbol. The currently received frequency is meant to denote the frequency that is received when the procedure of the method according to the invention commences. The method comprises a number of steps in a digital audio broadcasting receiver. First of all the test reception of the alternative frequency is performed. The test reception is mainly performed during a null symbol of a digital audio broadcasting frame of the currently received frequency. Preferably the test reception is only performed during a null symbol of the currently received frequency or alternatively the test reception is performed during a null symbol and at least during part of at least one phase reference symbol of the currently received frequency. After the test reception of the alternative frequency the test reception of the alternative frequency is evaluated. In one preferred method the alternative frequency is test received at least once before an evaluation of the test receptions. In another preferred method the alternative frequency is test received only once before the evaluation of the test reception. In yet another preferred method the alternative frequency is test received at least twice before an evaluation of the test receptions and the evaluation of the test receptions is based on a calculated tendency of the field strength of the alternative frequency. The method according to the invention thereby enables the an evaluation of an alternative frequency without interrupting the currently received programme/ information.

The aforementioned objects are achieved in accordance with the invention also by a device for test receiving

WO 99/14874

PCT/SE98/01624

15

alternative reception frequencies in a digital audio
broadcasting system receiver for the purpose of being able
to evaluate alternative reception frequencies. The
receiver tuned to a currently received frequency in a
5 digital audio broadcasting system format receives a current
programme/ information. The DAB format of the currently
received frequency comprises transmission frames. Each
transmission frame comprises multicarrier symbols and a
coarse synchronisation symbol in the form of a null symbol.
10 The currently received frequency is meant to denote the
frequency that is received before the device commences to
test receive alternative frequencies according to the
invention. The device comprises means for determining a
list of alternative frequencies. The list might consist of
15 only one alternative frequency or a plurality. The
currently received frequency can advantageously be included
in the list. The list might be assembled from all or only
selected frequencies from those included in the information
received by the currently received DAB transmission,
20 preprogrammed frequencies, one or more random frequencies
generated, for example, from a random generator, all or
only selected frequencies in the neighbourhood of the
currently received frequency, or all or only selected
frequencies in the frequency range of the digital audio
25 broadcasting receiver or a combination of any of these
possibilities. The device further comprises means for
systematically performing test receptions of the
alternative frequencies on the determined list. The test
receptions are mainly performed during the null symbols of
30 the digital audio broadcasting frames of the currently
received frequency. The device also comprises means for
evaluating the test receptions of the alternative
frequencies on the determined list. The evaluation can be
performed either after or interleaved with the the test
35 receptions of the alternative frequencies. Thereby the
device is able to perform an evaluation of alternative

WO 99/14874

PCT/SE98/01624

16

frequencies on a determined list without interrupting the currently received programme/information. In some embodiments of the invention the device preferably further comprises means for determining which one of the alternative frequencies or the currently received frequency is preferable from a field strength point of view. The determination is based on the evaluation of the test receptions of the alternative frequencies on the determined list. The device is thereby enabled to deliver a preferable alternative frequency for a current programme/information in a digital audio broadcasting receiver without interrupting the current programme/information. In other embodiments of the invention the device preferably further comprises means for changing the reception frequency to the determined preferable reception frequency. Preferably the means for changing the reception frequency to the determined preferable reception frequency executes a change of frequency inbetween two digital audio broadcasting frames of the currently received frequency. The device is thereby able to automatically change the reception frequency in a digital audio broadcasting receiver without any interruption or only a practically unnoticeable interruption of the current programme. In some embodiments the means for systematically performing the test receptions only performs test receptions during the null symbols of the currently received frequency. In other embodiments the means for systematically performing the test receptions performs test receptions during the null symbols and at least during part of at least one phase reference symbol of the currently received frequency. In some embodiments the means for systematically performing test receptions systematically performs test receptions of the alternative frequencies at least once each before the means for evaluating the test receptions evaluates the test receptions. In other embodiments the means for systematically performing test receptions systematically

WO 99/14874

PCT/SE98/01624

17

performs test receptions of the alternative frequencies only once each before the means for evaluating the test receptions evaluates the test receptions. In alternative embodiments the means for systematically performing test
5 receptions systematically performs test receptions of the alternative frequencies at least twice each before the means for evaluating the test receptions evaluates the test receptions and that the means for evaluating the test
10 receptions bases its evaluation on a calculated tendency of the field strength of each alternative frequency on the determined list. Preferably at least one alternative frequency on the determined list is a digital audio
15 broadcasting system transmission and where the transmission frames of the different digital audio broadcasting systems comprises transmitter identification information during the null symbols which transmitter identification information
is used by the means for evaluating the test receptions. In some circumstances at least one of the alternative frequencies on the determined list is of the FM or AM radio
20 broadcasting type and that the means for evaluating the test receptions further determines what type of broadcasting system each alternative frequency broadcasts.

By providing a device and a method for test receiving alternative frequencies without interrupting the current
25 programme, a plurality of advantages over prior art systems are obtained. Depending on how the frames are synchronised between the current reception frequency and an alternative frequency to which a change is to be performed, a more or
less unnoticeable change can be executed. Under favourable
30 conditions even a data transfer can be changed from one reception frequency to another without any loss of information. The device and method according to the invention will work just as well in a mobile receiver as in a stationary receiver. A stationary receiver might be
35 located in an area which is an intersection of two or more

WO 99/14874

PCT/SE98/01624

18

5 broadcasting areas with different transmitter frequencies
in such a way that under certain conditions, weather
conditions for example, one reception frequency is better
than the other(s), and under different conditions another
10 reception frequency is superior. The invention can also
advantageously be utilised in a single frequency network
where a full coverage DAB network is not yet achieved and
where analog FM or AM broadcasting is utilised to
complement the DAB network and thereby provide complete
15 coverage for regional and/or national programmes. The
difference being that test receptions are performed on
alternative FM or AM frequencies instead of on DAB frames
and that the evaluation of the test receptions are adapted
according to the type of test reception performed.

15 DESCRIPTION OF THE FIGURES

The invention will now be described in more detail for
explanatory, and in no sense limiting, purposes, with
reference to the following figures, in which

- Fig. 1 shows a block diagram of one DAB frame,
- 20 Fig. 2 shows a frequency coverage map,
- Fig. 3 temporally shows null symbols of several
different transmitting frequencies,
- Fig. 4 shows a block diagram of a receiver according to
the invention, and
- 25 Fig. 5 shows a flow chart of how the reception
frequency in a receiver is changed according to
one method of the invention.

WO 99/14874

PCT/SE98/01624

20

and differential quadrature phase-shift keying (QPSK) modulation onto a a large number of carriers to form the DAB signal.

5 Due to, among other things, the interleaving, not only within a single frame but also between different frames, the fast information channel 103 and the main service channel 104 cannot be interrupted for any substantial length of time without causing a substantial interruption of the received programme/information before the
10 interleaving is complete again.

As mentioned previously, the null symbol 101 is used for coarse synchronisation and was originally intended to be completely empty, as the name implies. Later revisions of the DAB standard has introduced the possibility to use the
15 null symbol 101 for transmitter identification. Transmitter identification is accomplished by transmitting a TII specific for the transmitter in question during the null symbol 101. This means that in an SFN the only deviating information transmitted by the transmitters is
20 the TII during the null symbol and therefore the TII is coded in a special way and transmitted at a low power level to thereby avoid any interference problems and to enable the null symbol 101 to still function as a null symbol. According to the invention test receptions can be performed
25 during the null symbol 101 and possibly during part of the synchronisation symbol 102 without interfering with the currently received programme and its necessary information carrying parts 103, 104. Test receptions of other frequencies can only be performed when the current
30 programme is not disturbed since only one reception chain necessary and used according to the invention.

Figure 2 shows a frequency coverage map over four different broadcasting regions 211, 212, 213, 214, each region broad-

WO 99/14874

PCT/SE98/01624

21

casting with a different frequency. Each broadcasting region 211, 212, 213, 214, has at least one transmitter 221, 231, 222, 232, 242, 223, 224. A first broadcasting region 211 comprises two transmitters 221, 231, to be able to cover the whole first region 211. The two transmitters 221, 231, of the first region 211 transmit at the same frequency and thereby takes advantage of the DAB system. A second broadcasting region 212 comprises three transmitters 222, 232, 242, to cover the whole second region 212. The number of necessary transmitters can, for example, depend on the geography of the region or transmitter output power level. The first and second regions 211, 212, are single frequency networks on a small scale.

Each one of the third and fourth broadcasting regions 213, 214, comprises a single respective transmitter 223, 224. These broadcasting regions 213, 214 can be of the DAB, FM, or AM type. The invention is not restricted to what type of broadcasting system a mobile receiver enters or a stationary receiver is in the vicinity of, but only that the currently received programme is transmitted from a DAB system since the invention deals with performing test receptions of alternative frequencies without interruption of the received DAB frames. It will be assumed in the following that all of the broadcasting regions 211, 212, 213, 214, are of the DAB type. Further it will be assumed that at least two of the broadcasting regions 211, 213, (the first and third 211, 213) broadcast at least one common programme/ information channel, the programme being the one that our mobile receiver 290 is receiving when travelling along a road 200 that goes through the first and third broadcasting regions 211, 213, in our example.

If the same programme is not available, a receiver would preferably change to an alternative frequency that

WO 99/14874

PCT/SE98/01624

22

transmits the same type of programme that is currently received. In these circumstances it would be preferable if the change to an alternative frequency is a bit more reluctant, i.e. the current frequency and therefore current programme would be allowed to degrade a bit more before a change is performed than when the same programme is available and a change back and forth can be performed without, for example, a listener noticing these changes. The DAB standard has provisions for not only broadcasting alternative frequencies that transmit the same programme to the receiver, but also alternative frequencies that transmit the same type of programme, i.e. news, pop music, jazz, sport etc.

Test receptions of alternative frequencies is preferably done continuously, but change to an alternative frequency will usually only be close at hand when a receiver is located in a region/intersection 219 between two or more broadcasting regions 211, 213, as is illustrated in figure 2. According to the invention, test receptions of alternative frequencies are performed during the null symbols of the currently received DAB frames. Figure 3 temporally illustrates null symbols of several different transmitting frequencies 351, 352, 353, 354, where the top one 351 is assumed to be the currently received DAB frequency 351 with its DAB frames and corresponding null symbols 311, 321, 331, 341 occurring during respective time periods 310, 320, 330, 340. The other three frequencies 352, 353, 354, can, for example, correspond to the respective broadcasting regions 212, 213, 214, of figure 2, which have been broadcasted as alternative frequencies. They can be alternative frequencies if they, for example, transmit the same programme/information, the same type of programme, or just be something that broadcasts something.

WO 99/14874

PCT/SE98/01624

24

third 353 and fourth 354 frequencies are performed during the current 351 frequency's third 331 and fourth 341 null symbols which occur at the third 330 and fourth 340 time periods respectively. During the third 330 and fourth 340 time periods, if the third and fourth frequencies are somewhat in synchronisation with the currently 351 received frequency, their null symbols 333, 344 and their respective TII's 363, 364 will be received and evaluated.

This procedure can be repeated several times until the receiver determines that an alternative frequency will provide a superior reception quality compared to the currently received frequency, which is when a change of reception frequency is initiated. In the example, as illustrated by figures 2 and 3, a changeover to the third alternative frequency 353 broadcasted in the third region 213 is a probable outcome. As mentioned previously, the alternative frequencies are not necessarily DAB transmissions and even if they are, it is not necessary for the invention that they are synchronised. The receiver performs test receptions of alternative frequencies during the null symbols of the currently received DAB transmission and frequency. Independently of what is received during these test receptions of the alternative frequencies, an evaluation of the received signals is performed. A prediction as to the tendency, stronger and stronger or weaker and weaker, of the received signal can also possibly be done to support the determination as to what frequency a change should be executed to and also when this should happen. Depending on the specific embodiment of the invention, the evaluation may comprise a determination of what type of signals are received, i.e. DAB, FM, or AM, so that an evaluation may take into account not only the received signal strength but also the received signal strength in view of the type of received signals. The determination of what type of signals that are received can

WO 99/14874

PCT/SE98/01624

25

be performed by using fast fourier transform (FFT) for a frequency analysis over time and/or an attempt at decoding the received signals.

Figure 4 shows a block diagram of a receiver according to the invention. The receiver will preferably either comprise an antenna 470 or means for connecting an external antenna. Signals picked up by the antenna 470 will preferably first of all be amplified in a preamplifier/tuner 471 which preferably comprises mixing means for transposing the received signals to an intermediate frequency (IF). The heart of a DAB receiver will process its signals in a digital form and if a quadrature demodulator 472 is realised in digital form the quadrature demodulator 472 will have an analog to digital converter (A/D converter) at the input or if the quadrature demodulator 472 is realised in analog form then it will have an analog to digital converter on its output. The processing according to the invention is performed digitally by a digital signal processing means 473 preferably in conjunction with the ordinary digital signal processing that is required for extracting the received programme/information in a robust manner. Assuming that this is a DAB radio receiver, then the extracted programme, which is in a digital format, needs to be converted to analog signals in a digital to analog converter (D/A converter) 474. Unless very low levels of sound is adequate, then the analog signals needs to be amplified in an amplifier 475 before the analog signals are fed to a speaker 476, headphones, or the like.

The present invention can be put into apparatus-form either as pure hardware, as pure software or as a combination of hardware and software. If the method according to the invention is realised in the form of software, it can be completely independent or it can be one part of a larger

WO 99/14874

PCT/SE98/01624

26

programme. The software can suitably be located in a general purpose computer or in a dedicated computer.

Fig. 5 shows a flow chart of how the reception frequency in a receiver is changed according to one method of the invention. In an optional field strength measuring step 580, the field strength of the currently received frequency is measured. Thereafter in an optional field strength test step 581, the measured field strength of the currently received frequency is either compared to a fixed threshold value or used in a field strength prediction computation with which a tendency is computed and thereafter compared with model tendencies. If the field strength is above the fixed threshold or does not show a weakening tendency, then the procedure returns to field strength measuring step 580. On the other hand, if the field strength is below a fixed threshold or shows a weakening tendency, then the procedure proceeds to null symbol step 582 which will be described in full below. These two optional steps 580, 581 are optional, the method according to the invention, as described below, can be performed continuously, initiated by another program, or initiated on demand by other methods/ devices than by the method which has been described in relation to the two optional steps 580, 581.

When it is determined that test receptions of alternative frequencies should be performed, for example according to the previously described optional steps 580, 581, then it is determined, in a null symbol step 582, when in time the null symbols appear. According to the invention, in order not to interrupt the reception of the currently received programme/ information, test receptions of alternative frequencies are performed during the null symbols of the currently received DAB frames. By using the null symbol the information transfer part of the DAB frame is not interrupted and only the TII of the currently received

WO 99/14874

PCT/SE98/01624

27

frequency is lost for that frame. The TII is probably the only part of a DAB frame that will be the same when DAB frames are received from the same transmitter, the loss of the TII from a few frames will not affect the reception in any way. When the temporal location of the null symbols have been identified, then the reception frequency of the receiver is switched to an alternative frequency, during a null symbol and only during the null symbol, in an alternative frequency step 583. The alternative frequency that is switched to will preferably come from a list that is maintained by the receiver by means of information received from DAB. During the null symbol, signals are received from the alternative frequency and measured and analysed in a measuring step 584. Before the end of the null symbol the receiver switches reception frequency back to the currently received frequency in a switch-back step 585, for reception of the information carrying part of the frame.

When the receiver is once again receiving the currently received programme/ information, a more alternatives test step 586 tests if there are more alternative frequencies to perform a test reception on. If there are more alternative frequencies, then the procedure preferably continues, either with the null symbol step 582 or with the alternative frequency step 583 depending on the specific implementation. On the other hand, if there are no more alternative frequencies, then the procedure continues to a determination step 587. The determination step 587 analyses the measurements which were taken during the measurement step 585 on the alternative frequencies and preferably the field strength measurements taken on the currently received frequency and determines in view of all the measurements if a switch/ change of reception frequency should be done and if so to what alternative frequency. A change reception frequency test step 588 will direct the

WO 99/14874

PCT/SE98/01624

28

5 procedure in the correct direction in view of the outcome
of the determination step 587. If it is determined that
the receiver should change reception frequency, then the
procedure continues to a change reception frequency step
10 589. If, on the other hand, the circumstances are such
that the currently received frequency is still that which
is preferable, then the procedure continues either to step
580, step 582, or step 583, or to something completely
different, all depending on the specific implementation of
the invention.

As a summary, the invention can basically be described as
a device and a method which provide means to enable a
change of reception frequency without any or very little
interruption to the received programme.

15 The invention is not limited to the embodiments described
above but may be varied within the scope of the appended
patent claims.

WO 99/14874

PCT/SE98/01624

29

109810.pct spb 980909.

FIG 1

	101	null symbol
	102	phase reference symbol
5	103	FIC fast information channel
	104	MSC main service channel - audio programmes

FIG 2

	200	road
	211	frequency 1 coverage
10	212	frequency 2 coverage
	213	frequency 3 coverage
	214	frequency 4 coverage
	219	overlap between 211 and 213
	221	transmitter 1 frequency 1
15	222	transmitter 1 frequency 2
	223	transmitter 1 frequency 3
	224	transmitter 1 frequency 4
	231	transmitter 2 frequency 1
	232	transmitter 2 frequency 2
20	242	transmitter 3 frequency 2
	290	receiver / mobile receiver / car

FIG 3

	310	time 1
	311	null symbol at time 1 for frequency 1
25	320	time 2
	321	null symbol at time 2 for frequency 1
	322	null symbol at time 2 for frequency 2
	330	time 3
	331	null symbol at time 3 for frequency 1
30	333	null symbol at time 3 for frequency 3

WO 99/14874

PCT/SE98/01624

30

340 time 4
 341 null symbol at time 4 for frequency 1
 344 null symbol at time 4 for frequency 4
 351 frequency 1
 5 352 frequency 2
 353 frequency 3
 354 frequency 4
 361 tii at time 1 frequency 1
 362 tii at time 2 frequency 2
 10 363 tii at time 3 frequency 3
 364 tii at time 4 frequency 4

FIG 4

470 antenna
 471 preamplifier
 15 472 A/D converter
 473 digital signal processing
 474 D/A converter
 475 amplifier
 476 speaker

20 FIG 5

580 optional - field strength measuring step
 581 optional - field strength test step
 582 null symbol step
 583 alternative frequency step
 25 584 measurement step
 585 switch back step
 586 more alternative frequencies test step
 587 determination step
 588 change reception frequency test step
 30 589 change reception frequency step!

WO 99/14874

PCT/SE98/01624

31

CLAIMS

1. A method for providing an automatic change of
 5 reception frequency in a digital audio broadcasting system
 receiver between a currently received frequency in a
 digital audio broadcasting system format comprising
 transmission frames where each transmission frame comprises
 multicarrier symbols and a coarse synchronisation symbol in
 10 the form of a null symbol, to a, from a field strength
 point of view, preferable alternative reception frequency,
 characterized in that the method comprises the following
 steps in a digital audio broadcasting receiver:
- determining a list of alternative frequencies;
 - 15 - systematically performing test receptions of the
 alternative frequencies on the determined list and
 performing the test receptions mainly during the null
 symbols of the digital audio broadcasting frames of
 the currently received frequency;
 - 20 - evaluating the test receptions of the alternative
 frequencies on the determined list;
 - based on the evaluation of the test receptions of the
 alternative frequencies on the determined list
 determining which one of the alternative frequencies
 25 or the currently received frequency is preferable from
 a field strength point of view;
 - changing the reception frequency to the determined
 preferable reception frequency;
- 30 thereby enabling an automatic change of reception frequency
 in a digital audio broadcasting receiver without any
 interruption or only a practically unnoticeable
 interruption of the current programme.

SUBSTITUTE SHEET (rule 26)

WO 99/14874

PCT/SE98/01624

32

2. The method according to claim 1, characterized in that the test receptions are only performed during the null symbols of the currently received frequency.
- 5 3. The method according to claim 1, characterized in that the test receptions are performed during the null symbols and at least during part of at least one phase reference symbol of the currently received frequency.
- 10 4. The method according to any one of claims 1 to 3, characterized in that the changing of reception frequency to the determined preferable reception frequency is performed inbetween two digital audio broadcasting frames of the currently received frequency.
- 15 5. The method according to any one of claims 1 to 4, characterized in that the alternative frequencies on the determined list are systematically test received at least once each before the evaluation of the test receptions.
- 20 6. The method according to any one of claims 1 to 4, characterized in that the alternative frequencies on the determined list are systematically test received only once each before the evaluation of the test receptions.
- 25 7. The method according to any one of claims 1 to 4, characterized in that the alternative frequencies on the determined list are systematically test received at least twice each before the evaluation of the test receptions and that the evaluation of the test receptions is based on calculated tendency of the field strength of each alternative frequency on the determined list.
- 30 8. The method according to any one of claims 1 to 7, characterized in that at least one alternative frequency on the determined list is a digital audio broadcasting system

SUBSTITUTE SHEET (rule 26)

WO 99/14874

PCT/SE98/01624

33

transmission and where the transmission frames of the different digital audio broadcasting systems comprises transmitter identification information during the null symbols and which frames are in principle synchronised.

- 5 9. The method according to any one of claims 1 to 8, characterized in that at least one of the alternative frequencies on the determined list is of the FM or AM radio broadcasting type and that the evaluation of the test
- 10 receptions further comprises the step of determining what type of broadcasting system each alternative frequency broadcasts.
- 15 10. A method for test receiving alternative reception frequencies in a digital audio broadcasting system receiver where a currently received frequency in a digital audio broadcasting system format comprises a current programme/information and comprises transmission frames where each transmission frame comprises multicarrier symbols and a coarse synchronisation symbol in the form of a null symbol, for the purpose of being able to determine a from a field
- 20 strength point of view preferable alternative reception frequency, characterized in that the method comprises the following steps in a digital audio broadcasting receiver:
- determining a list of alternative frequencies;
 - systematically performing test receptions of the

25 alternative frequencies on the determined list and performing the test receptions mainly during the null symbols of the digital audio broadcasting frames of the currently received frequency;

 - evaluating the test receptions of the alternative

30 frequencies on the determined list;

 - based on the evaluation of the test receptions of the alternative frequencies on the determined list determining which one of the alternative frequencies

SUBSTITUTE SHEET (rule 26)

WO 99/14874

PCT/SE98/01624

34

- or the currently received frequency is preferable from
a field strength point of view;
thereby enabling the delivery of a preferable alternative
frequency in a digital audio broadcasting receiver for a
current programme/information without interrupting the
current programme/information.
11. The method according to claim 10, characterized in
that the test receptions are only performed during the null
symbols of the currently received frequency.
12. The method according to claim 10, characterized in
that the test receptions are performed during the null
symbols and at least during part of at least one phase
reference symbol of the currently received frequency.
13. The method according to any one of claims 10 to 12,
characterized in that the alternative frequencies on the
determined list are systematically test received at least
once each before the evaluation of the test receptions.
14. The method according to any one of claims 10 to 12,
characterized in that the alternative frequencies on the
determined list are systematically test received only once
each before the evaluation of the test receptions.
15. The method according to any one of claims 10 to 12,
characterized in that the alternative frequencies on the
determined list are systematically test received at least
twice each before the evaluation of the test receptions and
that the evaluation of the test receptions is based on
calculated tendency of the field strength of each
alternative frequency on the determined list.
16. The method according to any one of claims 10 to 15,
characterized in that at least one alternative frequency on

SUBSTITUTE SHEET (rule 26)

WO 99/14874

PCT/SE98/01624

35

the determined list is a digital audio broadcasting system transmission and where the transmission frames of the different digital audio broadcasting systems comprises transmitter identification information during the null symbols and which frames are in principle synchronised.

17. The method according to any one of claims 10 to 16, characterized in that at least one of the alternative frequencies on the determined list is of the FM or AM radio broadcasting type and that the evaluation of the test receptions further comprises the step of determining what type of broadcasting system each alternative frequency broadcasts.

18. A method for test receiving alternative reception frequencies in a digital audio broadcasting system receiver where a currently received frequency in a digital audio broadcasting system format comprises a current programme/information and comprises transmission frames where each transmission frame comprises multicarrier symbols and a coarse synchronisation symbol in the form of a null symbol, for the purpose of being able to evaluate alternative reception frequencies, characterized in that the method comprises the following steps in a digital audio broadcasting receiver:

- determining a list of alternative frequencies;
- systematically performing test receptions of the alternative frequencies on the determined list and performing the test receptions mainly during the null symbols of the digital audio broadcasting frames of the currently received frequency;
- evaluating the test receptions of the alternative frequencies on the determined list;

thereby enabling an evaluation of alternative frequencies on a determined list without interrupting the currently received programme/information.

SUBSTITUTE SHEET (rule 26)

WO 99/14874

PCT/SE98/01624

36

19. The method according to claim 18, characterized in that the test receptions are only performed during the null symbols of the currently received frequency.

5 20. The method according to claim 18, characterized in that the test receptions are performed during the null symbols and at least during part of at least one phase reference symbol of the currently received frequency.

10 21. The method according to any one of claims 18 to 20, characterized in that the alternative frequencies on the determined list are systematically test received at least once each before the evaluation of the test receptions.

15 22. The method according to any one of claims 18 to 20, characterized in that the alternative frequencies on the determined list are systematically test received only once each before the evaluation of the test receptions.

20 23. The method according to any one of claims 18 to 20, characterized in that the alternative frequencies on the determined list are systematically test received at least twice each before the evaluation of the test receptions and that the evaluation of the test receptions is based on calculated tendency of the field strength of each alternative frequency on the determined list.

25 24. The method according to any one of claims 18 to 23, characterized in that at least one alternative frequency on the determined list is a digital audio broadcasting system transmission and where the transmission frames of the different digital audio broadcasting systems comprises transmitter identification information during the null symbols and which frames are in principle synchronised.

SUBSTITUTE SHEET (rule 26)

WO 99/14874

PCT/SE98/01624

37

25. The method according to any one of claims 18 to 24, characterized in that at least one of the alternative frequencies on the determined list is of the FM or AM radio broadcasting type and that the evaluation of the test
5
receptions further comprises the step of determining what type of broadcasting system each alternative frequency broadcasts.

26. A method for test receiving an alternative reception frequency in a digital audio broadcasting system receiver
10
where a currently received frequency in a digital audio broadcasting system format comprises a current programme/information and comprises transmission frames where each transmission frame comprises multicarrier symbols and a coarse synchronisation symbol in the form of a null symbol,
15
for the purpose of being able to evaluate an alternative reception frequency, characterized in that the method comprises the following steps in a digital audio broadcasting receiver:

- performing a test reception of the alternative
20
frequency mainly during a null symbol of a digital audio broadcasting frame of the currently received frequency;
- evaluating the test receptions of the alternative frequency;
- 25
thereby enabling an evaluation of an alternative frequency without interrupting the currently received programme/information.

27. A device for test receiving alternative reception frequencies in a digital audio broadcasting system receiver
30
where a currently received frequency (351) in a digital audio broadcasting system format comprises a current programme/information and comprises transmission frames where each transmission frame comprises multicarrier symbols and a coarse synchronisation symbol in the form of

SUBSTITUTE SHEET (rule 26)

WO 99/14874

PCT/SE98/01624

38

a null symbol (101), for the purpose of being able to evaluate alternative reception frequencies, characterized in that the device comprises:

- 5 - means (473) for determining a list of alternative frequencies;
- means (473) for systematically performing test receptions of the alternative frequencies on the determined list and performing the test receptions mainly during the null symbols of the digital audio broadcasting frames of the currently received frequency;
- 10 - means (473) for evaluating the test receptions of the alternative frequencies on the determined list;
- thereby enabling an evaluation of alternative frequencies on a determined list without interrupting the currently received programme/information.
- 15

28. The device according to claim 27, characterized in that the device further comprises means for determining which one of the alternative frequencies or the currently received frequency is preferable from a field strength point of view, based on the evaluation of the test receptions of the alternative frequencies on the determined list, thereby enabling the delivery of a preferable alternative frequency in a digital audio broadcasting receiver for a current programme/information without interrupting the current programme/information.

20

25

29. The device according to claim 28, characterized in that the device further comprises means for changing the reception frequency to the determined preferable reception frequency, thereby enabling an automatic change of reception frequency in a digital audio broadcasting receiver without any interruption or only a practically unnoticeable interruption of the current programme.

30

SUBSTITUTE SHEET (rule 26)

35. The device according to any one of claims 27 to 32,
30 characterized in that the means for systematically
performing test receptions systematically performs test

FROM ARMSTRONG, KRATZ, QUINTOS, HANSON & BROOKS (THU) 1. 5 06 16:42/ST. 16:02/NO. 4863196078 P118
 9914874A < 1 1A 168168
 BNSDOCID: <WQ

WO 99/14874

PCT/SE98/01624

40

5 receptions of the alternative frequencies at least twice
each before the means for evaluating the test receptions
evaluates the test receptions and that the means for
evaluating the test receptions bases its evaluation on a
calculated tendency of the field strength of each
alternative frequency on the determined list.

10 36. The device according to any one of claims 27 to 35,
characterized in that at least one alternative frequency on
the determined list is a digital audio broadcasting system
transmission and where the transmission frames of the
different digital audio broadcasting systems comprises
transmitter identification information during the null
symbols which transmitter identification information is
used by the means for evaluating the test receptions.

15 37. The device according to any one of claims 27 to 36,
characterized in that at least one of the alternative
frequencies on the determined list is of the FM or AM radio
broadcasting type and that the means for evaluating the
test receptions further determines what type of
20 broadcasting system each alternative frequency broadcasts.

SUBSTITUTE SHEET (rule 26)

WO 99/14874

PCT/SE98/01624

1/3




FIG. 1




FIG. 2

WO 99/14874

PCT/SE98/01624

2/3




FIG.3




FIG.4

WO 99/14874

PCT/SE98/01624

3/3




FIG.5

INTERNATIONAL SEARCH REPORT

International application No.

PCT/SE 98/01624

A. CLASSIFICATION OF SUBJECT MATTER

IPC6: H04H 1/00

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC6: H04H

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

SE,DK,FI,NO classes as above

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	EP 0689308 A1 (NOKIA TECHNOLOGY GMBH), 27 December 1995 (27.12.95), page 2, line 43 - page 3, line 23; page 3, line 55 - page 4, line 9; page 4, line 40 - page 5, line 10, page 7, line 41 - page 8, line 16 --	1-37
A	EP 0666661 A2 (GRUNDIG E.M.V.), 9 August 1995 (09.08.95), column 3, line 1 - line 15; column 3, line 51 - column 4, line 1; column 4, line 30 - line 54, abstract --	1-37
A	Electronics & Wireless World, Volume 92, No 1609, November 1986, (London), D.T. Wright et al, "BROADCAST RADIO-DATA", see BBC plans for RDS --	1-37



Further documents are listed in the continuation of Box C.



See patent family annex.

* Special categories of cited documents:

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier document but published on or after the international filing date
- "I" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

"I" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance: the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search

21 January 1999

Date of mailing of the international search report

25 -01- 1999

Name and mailing address of the ISA/

Swedish Patent Office

Box 5055, S-102 42 STOCKHOLM

Facsimile No. +46 8 666 02 86

Authorized officer

Peter Hedman

Telephone No. +46 8 782 25 00

Form PCT/ISA/210 (second sheet) (July 1992)

INTERNATIONAL SEARCH REPORT

International application No.

PCT/SE 98/01624

C (Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT		
Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 5465396 A (BILLIE J. HUNSINGER ET AL), 7 November 1995 (07.11.95) -- -----	9,17,25,37

Form PCT/ISA/210 (continuation of second sheet) (July 1992)

INTERNATIONAL SEARCH REPORT

Information on patent family members

01/12/98

International application No.

PCT/SE 98/01624

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
EP 0689308 A1	27/12/95	FI 942971 D	00/00/00
EP 0666661 A2	09/08/95	DE 4403408 C	23/02/95
US 5465396 A	07/11/95	EP 0679303 A	02/11/95
		JP 8505989 T	25/06/96
		US 5757854 A	26/05/98
		WO 9416506 A	21/07/94

Form PCT/ISA/210 (patent family annex) (July 1992)